


NOTES:

- MOLDED CONNECTOR END REQUIREMENTS:
  - A. INNER MOLD USING PE
  - B. COPPER FOIL WRAP AND 360° SOLDER TO CONNECTOR
  - C. PVC - 45P LIGHT BLUE
- CABLE: [28AWG (7/0.127)\*9P+AL/MY +DW(7/0.163)+85%BD(16/8/0.12)]TIN  
 WIRE: PP OD=0.75±0.05mm  
 COLOR: P1 COLOR CODE  
 JACKET: 80°C PVC OD=6.5±0.15mm  
 COLOR: LIGHT BLUE
- FINISHED PRODUCTS LENGTH:  
 (1) LENGTH=3048mm TOLERANCE:±50.8mm

PIN OUTS							
CN 26M	V35M	PAIR	WIER COLOR	CN 26M	V35M	PAIR	WIRE COLOR
1	P	1	BROWN	8	C	6	GRAY/BLACK
14	S		BROWN/WHITE	11	D	7	WHITE
2	U		RED	12	E		WHITE/BLACK
15	W	2	RED/BLACK	13	K		PINK
3	Y		YELLOW	26	B	8	PINK/BLACK
16	A A	3	YELLOW/BLACK	19			
4	V		GREEN	22	B	9	LIGHT BLUE
17	X	4	GREEN/BLACK	23			
5	R		BLUE	24			
18	T	5	BLUE/WHITE	6	F		LIGHT BLUE/BLACK
7	H	6	GRAY	shield	1(A), shield		



HVPS:300V INSULATION: UPON 100M ohm AND 100M ohm ELECTRIC CONDUCTION:INSIDE 5 ohm			
ITEM NO	PART NAMES	QTY	REMARK
1	CABLE: UL2919 LIGHT BLUE 9P OD=6.5±0.15mm	1PCS	
2	CONNECTOR:HPCN26P MALE NICKEL-PLATING, INSULATER COLOR:WHITE	1PCS	
3	CONNECTOR:V35 MALE, NICKEL-PLATING,INSULATER COLOR:BLACK	1PCS	
4	THUMBSCREW:4*53.5mm NICKEL-PLATING FEMALE	1PCS	
5	THUMBSCREW:4*53.5mm NICKEL-PLATING MALE	1PCS	
6	SCREW:5*47.7mm COLOR:BLACK	2PCS	

?	
?	
?	
?	

JDI TECHNOLOGIES	PRODUCT	10FT HPCN26M TO V35M	CUSTOMER		DRAWN	PXH	 THIRD ANGLE PROJECTION
	CUS,NO	SSV35MT-10	VERSION		CHECKED		
	DR,NO	SDSSV35MT-10	DRAWN DATE	MAR.10.2001	APPROVERD	Eric Lee	